

HANDHELD JAMMER

The SC09 boasts powerful counter-drone capabilities, capable of simultaneously disrupting the communications and navigation signals of multiple drone types and models. Combining advanced intelligent features with intuitive operation, it is an ideal counter-drone solution for a variety of scenarios, including field operations, public events, and VIP security.

EXTREME TEMPERATURES

WATERPROOF IP54

LIGHTWEIGHT

((△))
JAMMING

DISTINCTIVE ADVANTAGES

→ Lightweight

Total Weight: 4730g

→ Long-Range Jamming

Jamming range ≥ 1,500 meters

→ Multi-Mode Jamming

Manually Switchable Functions: Forced Landing, Return

→ Jamming Performance

Capable of jamming BeiDou and GLONASS satellite positioning signals.



HANDHELD JAMMER

SC 09 is a portable, ruggedized **LIGHTWEIGHT** ANTI-UAV GUN designed for military, law enforcement, and security professionals.

The handheld digital anti-drone jammer delivers rapid electromagnetic suppression across multiple frequency bands, including Beidou, and GLONASS. With a jamming range of over 1.5 km, quick response time (≤ 1.5 s), and versatile modes like forced landing and return-to-home, it ensures effective drone neutralization. Portable, rugged, and user-friendly, it features long battery life, integrated antennas, LCD status display, and compatibility with observation aids for precise operation in diverse environments.

**LIGHTWEIGHT**

Total weight is less than 5kg

**BEIDOU, GLONASS JAMMING**

Capable of jamming BeiDou and GLONASS satellite positioning signals

**JAM DRONES & CONTROLLERS**

For comprehensive neutralization of the threat

**PORTABLE**

All equipment fits in a dedicated ABS case for easy transport

**DURABILITY**

Full lifecycle ≥ 10 years

Specifications

WRJG-SC09

| | |
|---------------------------|---------------------------------|
| Frequency Coverage | ≥ 6 Channels |
| Transmission Power | 40 ± 2 dbm |
| Jamming Range | ≥ 1500 Meters |
| Standby Time | ≥ 30 Hours |
| Continuous Operating Time | ≥ 1.5 Hours |
| Operating Temperature | -20°C to 50°C / -4 °F to 122 °F |
| IP Rating | IP54 |
| Size | 665x265x65mm |
| Weight | 4730g |
| Durability | Full Lifecycle ≥ 10 Years |

* Depending on the RF environment & line of sight

* Please email us for more information